


SCR53 I

The Universal Connectivity Solution



Technical Data

Host Interface	Dual Mode <ul style="list-style-type: none">• Full speed USB (12 Mbps), bus powered• PnP RS232 (115,200 bps)• CCID compliant
Smart Card Interface	<ul style="list-style-type: none">• T=0, T=1 protocol support• Memory card support through SCM MCARD API• Communication speed up to 115,200 bps with serial interface (PPS, FI parameter)• Communication speed up to 344,105 bps with USB interface)• Frequency up to 12 MHz (PPS, DI parameter)• Support ISO 7816 Class A and AB smart card
Smart Card Connector	<ul style="list-style-type: none">• 8 contacts - ISO location• Certified for 100,000 insertions• Sliding contact
Human Interface	<ul style="list-style-type: none">• One dual state green LED
Cable/Power	Exchangeable cable <ul style="list-style-type: none">• 1.5m long with USB type A connector• 1.5m long with F-DB9 and Pass-through PS/2
Dimensions	<ul style="list-style-type: none">• LVH 90 x 70 x 16.5 mm
Operating Temperature	<ul style="list-style-type: none">• 0° to 50° Celsius
OS	<ul style="list-style-type: none">• Serial - Windows® 98, ME, NT4, 2000 and XP• - Windows® CE• - Solaris, Linux• USB - Windows® 98, ME, 2000, XP, Server 2003• - Windows® CE, MacOS, Linux, Solaris
API	<ul style="list-style-type: none">• PC/SC• CT-API (thru wrapper on top of PC/SC)• OCF upon request
Approvals	<ul style="list-style-type: none">• FCC Class B part 15, cULus, CE, VCCI• Microsoft® WHQL ME, 2000, XP• EMV Level I

Overview

The SCR53I is a logical extension of the new SCR33I and SCR13I smart card reader family based on SCM Microsystems' STC II micro controller. This device supports multiple interfaces, multiple reader devices and relevant security standards. Together, these features provide SCM Microsystems with the unique ability to offer an efficient, high performance, cost effective solution that combines USB and serial connections via a removable cable.

In addition, the SCR53I is the industry's first to offer on-board flash. This enables future firmware and application enhancements that guarantee against obsolescence. Taking full advantage of the STC II features, the SCR53I offers the best price/performance ratio in the market and helps reduce deployment and technical support costs.

SCR53I Benefits

- Dual host interface: USB and serial with exchangeable cable
- On-board flash provides seamless firmware upgrades in the field
- EMV Level I AND PC/SC certification based on a single solution
- High performance
- Fully tested and compliant with all major smart cards in the market
- Customizing options: casing, colors, and company logo

The SCM Microsystems' Advantage

SCM Microsystems brings over a decade of experience in ASIC and smart card reader development to this unique product, including:

- More than 80 patents
- Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and smart card industry leaders
- Industry endorsed SmartOS™ middleware
- Direct significant long-term relationships with all leading smart card manufacturers and application providers
- High quality mass production capability

US Headquarters
SCM Microsystems Inc.
466 Kato Terrace
Fremont, CA 94539 USA
email: scmsales@scmmicro.com
Phone +1 510 360 2300
Fax +1 510 360 0211

European Headquarters
SCM Microsystems GmbH
Oskar-Messter-Str. 13
D-85737 Ismaning, Germany
email: sales@scmmicro.de
Phone +49 89 9595 5000
Fax +49 89 9595 5555

SCM Microsystems Japan, Inc.
8F Hirakawacho Ronstate, 2-11-1,
Hirakawa-cho, Chiyoda-ku,
Tokyo, Japan 102-0093
email: sales@scmmicro.co.jp
Phone +81 3 3511 8511
Fax +81 3 3511 8516

SCM Microsystems France
ZE Athélie II
216, avenue du Serpolet
13704 La Ciotat Cedex - France
email: sales@scmmicro.fr
Phone +33 442 838 000
Fax +33 442 838 001

SCM Microsystems (Asia) Pte. Ltd.
25 Serangoon North Ave 5
#06-00 Keppel Digihub
Singapore 554914
email: sales@scmmicro.com.sg
Phone +65 6551 5233
Fax +65 6483 0210

SCM Microsystems India Pvt. Ltd.
Module No. 0506, 0507 & 0508
D' Block South, 5th Floor
Tidel Park, 4 Canal Bank Road
Taramani
Chennai 600113, India
email: sales@scmmicro.co.in
Phone +91 44 2254 0020
Fax +91 44 2254 0029

